PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau (



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: A01D 34/73, 34/67

(11) International Publication Number:

WO 96/24242

(43) International Publication Date:

15 August 1996 (15.08.96)

(21) International Application Number:

PCT/BE96/00012

A1

(22) International Filing Date:

9 February 1996 (09.02.96)

(30) Priority Data:

9500108

10 February 1995 (10.02.95)

(71) Applicant (for all designated States except US): SOLAR AND ROBOTICS S.A. [BE/BE]; Avenue de Fré 263, Botte postale 50, B-1180 Bruxelles (BE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): COLENS, André [BE/BE]; Rue Baillois 5, B-1330 Rixensart (BE).

(74) Agent: COLENS, Alain; Bureau Colens S.P.R.L., Rue Franz Merjay 21, B-1050 Bruxelles (BE).

CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AZ, BY, KG, KZ, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY,

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SELF CLEANING CUTTING HEAD FOR MOWERS



(57) Abstract

The invention relates to a cutting head, more particularly for a lawnmower with a rechargeable battery, comprising an electric motor (1) with a driving shaft (3) connected to a cutting disk (4) perpendicular to said shaft (3). The cutting disk (4) is provided with at least one blade (5) at its periphery. There is also provided a lower plate (7) parallel to and located under said cutting disk (4). The lower plate (7) is free wheeling around the axis through the use of a roller bearing (8). In the case of friction or jamming due to debris, the lower plate (7) starts to rotate to expel the debris by centrifugal effect.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IB	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI.	Côte d'Ivoire	u	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
		MN	Mongolia	UZ	Uzbekistan
FR	France				Viet Nam
GA	Gabon	MR	Mauritania	VN	Viet Nam

06/11/2003, EAST Version: 1.03.0007

Self cleaning cutting head for mowers.

5

The present invention relates to a self-cleaning cutting head and a lawnmower adapted with such head, more particularly a low consumption robotic lawnmower powered by an electric motor.

10

Lawnmowers with rechargeable batteries are designed in order to run with a minimum power. The cutting device must be adapted to this primary need. It is more particularly the case for mowers which are entirely robotic, with unattended operation, such as the ones described in the international patent application PCT/BE91/00068.

20

15

Traditional cutting systems perform the cutting operation under a cover, the cut grass being carried along by the rotating system. The ensuing result is that an important part of the energy is wasted during the cutting operation in order to transfer a kinetic energy to the cut grass which is dragged away by the cutting blade.

25

The cutting head usually used in robotic machines with a rechargeable battery is most often made of a lower plate, essentially circular, assembled to an upper plate by attaching flanges in such a way that a narrow space is left between the two plates.

0

5

10

15

25

0

A cutting disk is located between such plates and fixedly attached to a vertically extending output shaft from an electric motor. The cutting disk comprises preferably at least two retractable blades on its periphery, each of them pivoting around a shaft located on said periphery and capable of returning between said plates.

When the cutting disk starts to rotate, driven by the electric motor, the blades extend due to the centrifugal force and protrude out from both fixed plates in order to perform the grass cutting operation.

The rotating part in contact with the grass is then dramatically reduced and this arrangement decreases substantially the friction on the surface to be mowed, the carrying along or drawing away of the grass by the rotating system and the aerodynamic turbulences.

The use of such lower static plate entails however some problems.

In spite of the centrifugal effect due to the rotating disk, grass debris may on the long run and more particularly in wet weather, adhere to the internal face of the lower plate resulting in a braking effect with concomitant increase of energy consumption.

A low energy consumption is a vital criterion for an efficient performance of an electric lawnmower, more particularly a robotic mower with rechargeable battery.

5

In particular, for such an autonomous lawnmower with a battery which is rechargeable by induction at a fixed station, it is important than the search for this fixed station according to a predetermined algorithm (such as disclosed in patent application PCT/BE95/00013) be performed with a minimum energy consumption. For this purpose, the rotating cutting disk is disabled and will not operate during the searching step.

- The lower plate acts then as a crumb scoop and scrapes the surface to be mowed with ensuing penetration of earth, twigs or dead leave debris between the plates. This may create a problem when the cutting disk has to be restarted.
- The purpose of the present invention is to overcome the above mentioned disadvantages.

According to the invention, there is provided a cutting head comprising a cutting disk and at least one lower circular plate, preferably of similar dimension, wherein the static lower plate of the prior art is replaced by a mobile plate freely fixed at the end of the rotating shaft of the driving motor, for example by using a rolling bearing such a ball bearing a sliding bearing or a roller bearing.

The lower plate, in normal operation, which replaces the static lower plate of the prior art, is in contact with the grass of the surface to be moved and do not rotate, or only slightly.

This construction provides a simultaneous absence of friction between the rotating cutting disk and to decrease the aerodynamic friction.

- If debris becomes stuck between the lower plate and the cutting disk, the cutting disk will drag along the lower plate when the rotation starts at the beginning of a grass cutting operation, together with the debris which are then ejected by the rapid rotating movement. The rotating speed (for example 2,500 rotations per minute) is indeed of such an amplitude that no debris will remain between the cutting disk and the lower plate. The cutting head performs therefore as a self-cleaning cutting head.
- The accompanying drawing given by way of example is a view in cross-sectional elevation of a device according to the invention,
- The device comprises a motor 1 fixed to the chassis (not shown), possibly through an upper supporting plate 2. The motor is equipped with a shaft 3 at the end of which a cutting disk with retractable blades 5 is fixedly mounted.
- At the free end of the shaft, a lower circular plate 7 is mounted, which may freely rotate, through the use of a ball bearing 8. The plate 7 is parallel to the cutting disk and separated by a distance of p.e. 5 to 10 mm.
- Advantageously, the cutting head may be mounted slightly inclined forward in relation to the direction of movement of the mower such that there is a tilt angle of a few degrees between the spin axis and the perpendicular to the

WO 96/24242 PCT/BE96/00012

-5-

horizontal plane (the plane of the grass to be cut). Preferably the angle is between 4 and 10°, still preferably about 7°. The rear of the plates and cutting disk are therefore upswept and elevated over the mowed surface with no contact with the grass. According to this particular arrangement, the cutting blades will not touch again the grass at the rear of the cutting head, that is to say at a point opposite to the cutting operation, avoiding in this manner an additional energy consumption of poor efficiency.

10

5

This feature of the invention may also be applied independently to a cutting head of the prior art mower machine, with or without a lower plate.

The foregoing is considered as illustrative only of the principles of the invention. Since numerous modifications and changes will readily occur to those skilled in the art it is not desired to limit the invention tro the exact construction znd operation shown and described and accordingly, all suitable modifications and equivalents may be resorted to falling within the scope of the invention.

25

0

20

25

Claims :

- 1. A cutting head for mowers, more particularly lawnmowers, 5 comprising a motor and an output shaft which is connected to a cutting disk located perpendicularly to such shaft, said cutting disk comprising at its periphery at least one blade, said cutting head comprising also a lower plate cutting located under the 10 parallel to and characterised in that the lower plate is mounted in a free-rotating arrangement on said shaft by providing a roller bearing or equivalent means.
- 2. Cutting head according to claim 1 characterised in that the roller bearing is a ball bearing.
 - 3. Cutting head according to claims 1 or 2 characterised in that the peripheral blades are retractable towards the rotation axis.
 - 4. Cutting head according to any of the preceding claims characterised in that the rotation axis is inclined forwards relative to the direction of movement of the cutting head mounted in the mower.
 - 5. Lawnmower provided with a cutting head according to claims 1 to 4.
- 6. Lawnmower according to claim 5 characterised in that the motor is an electric motor supplied by a rechargeable battery.

WO 96/24242

PCT/BE96/00012

-7-

7. Lawnmower according to claim 5 or 6 characterised in that it is a autonomous robotic lawnmower.

8. Lawnmower according to claim 7 characterised in that the battery is recharged by induction at a fixed station.


10

15

20

25

0



06/11/2003, EAST Version: 1.03.0007

INTERNATIONAL SEARCH REPORT

International Application No PCT/BE 96/00012

-				_
,	ASSIFICATION OF SUBJECT MATTER			_
^	A 01 D 34/73,A 01 D 34/67			
Accordin	ng to International Patent Classification (IPC) or to both nation			
	DS SEARCHED	hal classification and IPCO		_
Minimun	n documentation searched (classification system followed by c	lassification symbols)		_
	. 01 D	, ,		
Documen	ntation searched other than minimum documentation to the ext	ent that such documents are inclu	ded in the fields searched	_
Electronic	c data base consulted during the international search (name of	data have and where perchant		_
		one one and, where practical, so	aren erms usea)	
	MENTS CONSIDERED TO BE RELEVANT			_
Category *	Citation of document, with indication, where appropriate, of	of the relevant passages	Relevant to claim No.	
				_
Х	DE, A, 4 021 496 (CLAAS SAULGAU GME	***	1,2	
	09 January 1992 (0	sn) 19.01-921		
	column : ines 7f	f;	İ	
Α	fig. 2,4 column 1 _ines 7f			
•	fig. 2,4.	I;	4	
v				
X	DE, A, 2 537 698 (JOSEF BAUTZ GMBH)		1,3	
j	03 March 1977 (03.	03.77).	Í	1
}	page 4, lines 6-25	; fig. 1,2.	1	1
A	US, A, 4 703 613			1
	(RAYMOND) 03 Novem	ber 1987	1,4,5,	1
	(03.11.87),			١
	fig. 1,3.		-	I
A	EP, A, 0 215 416		1,2,4	ĺ
			2,2,3	1
X Furthe	er documents are listed in the continuation of box C.	Patent family mem	bers are listed in annex.	1
Special cate	gones of ated documents :			┨
document consider	nt defining the general state of the art which is not red to be of particular relevance	OF DESCRIPTION OF STREET AND THE	d after the international filing date in conflict with the application but principle or theory underlying the	ł
cartier de	ocument but published on or effer the intermedical	mvenuon	• •	l
document	il which may throw doubte on an arrive doubte a	CHINDOL DE CONDIGERES IN	relevance; the claimed invention ovel or cannot be considered to p when the document is taken alone	l
auton o	or other special reason (as specified)	"Y" document of particular	relevance; the claimed invention involve an inventive step when the	ı
		QOCUMENT IS COMBINED	with one or more other such docu- n being obvious to a person skilled	
	t published prior to the international filing date but in the priority date claimed	in the art. "A" document member of th		l
te of the actual completion of the international search		Date of mailing of the international search report		
	10 June 1996		19. 07. 96	
ne and mail	ling address of the ISA	Authorized officer		ľ
	European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,	SCHNICEMANNI - L		
	Fac (+ 31-70) 340-3016	SCHNEEMANN e.h	1.	
		•		

Form PCT-ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

-2-

International pictation No PCT/BE 96/00012

	OCUMENTS CONSIDERED TO BE RELEVANT	
Category Citatio	n of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	(TODESCO, ANDREINA) 25 March 1987 (25.03.87), column 3, lines 46ff; fig. 2. WO, A, 92/04 817	1,7
	(COLENS, ANDRE) 02 April 1992 (02.04.92), page 21, lines 8ff; fig. 4 (cited in the application).	
		·

DUAHNA

ANNEX

ANNEXE

zum internationalen Recherchen-bericht über die internationale Fatentanmeldung Kr.

to the International Search Report to the International Patent Application No.

au rapport de recherche inter-national relatif à la demande de brevet international n'

PCT/BE 96/00012 SAE 128439

In diesem Anhang sind die Mitglieder der Patentfamilien der im obergenannten internationalen Recherchenbericht angeführten Patentdokumente angegeben. Diese Angaben dienen nur zur ühterrrichtung und erfolgen ohne Gewähr.

This Annex lists the patent family meebers relating to the patent documents cited in the above-mentioned international search report. The Office is in no may liable for these particulars which are given merely for the purpose of information.

La presente annexe indique les aembres de la famille de brevets relatifs aux documents de brevets cités dans le rapport de recherche international visée ci-dessus. Les reseignements fournis sont donnés à titre indicatif et n'engagent pas la responsibilité de l'Office.

ange P	führtes atent d in sear	rchenhericht Patentdokument ocument cited ch report e brevet cité port de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication	
	AI	4021496	09-01-92	EP A1 465790	15-01-92	
DE	AI	2537698	03-03-77	keine – none –	rien	
บร	A	4703613	03-11-87	CA A1 1247866 GB A0 8629137 GB A1 2183981 GB B2 2183981	03-01-89 14-01-87 17-06-87 11-10-89	
EP	AI	215416		keine – none –	rien	
WO	AI	9204817	02-04-92	AU A1 84 9-61/9188 9-61/958 9-84 9-61/958 9-84 9-61/9558 9-84 9-61/958 9-84 9-61/958 9-84 9-84 9-84 9-84 9-84 9-84 9-84 9-8	15-04-92 20-10-94 14-04-93 20-07-93 25-03-93 14-07-93 27-03-94 23-03-94 23-03-95 24-03-95 24-03-95 29-08-95	

06/11/2003, EAST Version: 1.03.0007

This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problems Mailbox.